

LPS[®] LPS 1[®]

GREASELESS LUBRICANT



Qualified to: Rolls Royce Engine Overhaul
Process 340 • Air Nippon Maintenance
Manual 75-31-02
Conforms to: Mil-C-23411A

PACKAGES

Net Fill	Part No.
11 oz. (312 grams) aerosol	00116
1 gal. (3.78 liters)	01128
5 gal. (18.93 liters)	00105
55 gal. (208 liters)	00155
20 fl.oz (591 ml) trigger spray	00122

APPLICATIONS

- Cables
- Circuit Breakers
- Electric Motors
- Electronic Connectors
- Generators
- Hinges
- Ignition Systems
- Locks
- Micrometers
- Molds
- Nuts and Bolts
- Precision Open Gears
- Power Tools
- Relays
- Sliding Mechanisms
- Switch Gears



PROPERTIES

Appearance/Physical State:

Clear straw-colored liquid

Dielectric Strength (ASTM D-877):

32 kv

Flash Point (TCC):

175°F (79°C)

HMIS:

1, 2, 0

Pour Point:

- 50°F (- 46°C)

Propellant:

Carbon Dioxide

Specific Gravity (water=1):

0.80 – 0.82

Typical Dried Film Thickness:

5 microns



Nonfood Compounds Program Listed
Category Code: H2 Registration
#059847 Aerosol, #129040 Bulk

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

4647 Hugh Howell Road • Tucker, GA 30084 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2012 LPS Laboratories • LPS[®] and LPS[®] 1[®] are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2013 • Rev. 5/2012